STATE OF ARKANSAS

Arkansas Geological Commission

Norman F. Williams, State Geologist

INFORMATION CIRCULAR 20-F

GEOLOGY OF THE GREENWOOD QUADRANGLE
ARKANSAS - OKLAHOMA

by.

Boyd R. Haley and Thomas A. Hendricks
U. S. GEOLOGICAL SURVEY



Prepared in cooperation with the U.S. Geological Survey

1968

(also published as U. S. Geological Survey Professional Paper 536-A)

STATE OF ARKANSAS

Arkansas Geological Commission

Norman F. Williams, State Geologist

INFORMATION CIRCULAR 20-F

GEOLOGY OF THE GREENWOOD QUADRANGLE ARKANSAS - OKLAHOMA

by

Boyd R. Haley and Thomas A. Hendricks
U. S. GEOLOGICAL SURVEY

OS 9

Prepared in cooperation with the U.S. Geological Survey

1968

(also published as U. S. Geological Survey Professional Paper 536-A)

COMMISSION MEMBERS ARKANSAS GEOLOGICAL COMMISSION

V. S. Parham - Chairman	Magnolia, Arkansas
Donald L. Libbey - Vice Chairman	Hot Springs, Arkansas
Albert J. Hess	Little Rock, Arkansas
Glen Hinkle	Mountain View, Arkansas
Dr. C. E. Ripley	Crossett, Arkansas
David L. Vosburg	Jonesboro, Arkansas
C. S. Williams	Mena. Arkansas

CONTENTS

	Page		Page
Abstract	A 1	Stratigraphy—Continued	
Introduction	1	Devonian and Mississippian Systems, Chattanooga	
Stratigraphy	2	Shale	A 6
Cambrian System	2	Mississippian System	6
Ordovician System	3	Post-Chattanooga pre-Pitkin formations	6
Van Buren Formation and Gasconade Dolomite		Pitkin Limestone	7
undifferentiated	3	Pennsylvanian System	7
Roubidoux Formation	3	Morrow Series	7
Jefferson City Dolomite	3	Atoka Series, Atoka Formation	7
Cotter Dolomite	3	Des Moines Series, Krebs Group	7
Powell Dolomite	3	Quaternary System	9
Everton Formation	3	Terrace deposits	9
St. Peter Sandstone	3	Alluvium	9
Joachim Dolomite	3	Structure	9
Plattin Limestone	6	Economic geology	10
Fernyale Limestone	6	Coal	10
Cason Shale	6	Oil and gas	12
	0	Building stone	12
Silurian and Devonian Systems, St. Clair Limestone	_	Road metal	15
and undifferentiated rocks	6	Gravel, sand, and clay	15
Devonian System, Penters Chert	6	References cited	15
PLATE 1. Geologic map of Greenwood quadrangle. 2. Stratigraphic sections in Greenwood quadrang.		in pocket]	
3. Structure-contour, coal-bed, and gas-field-map		onwood anadranala	
4. Structural sections in Greenwood quadrangle.	or Gre	enwood quadrangie.	Page
			A2
•		e Greenwood quadrangle and vicinity	8
	TAE	BLES	
			Page
			Page A4
		quadrangle	10
3. Estimated remaining reserves of coal in the L	ower H	od quadrangleartshorne coal bed in the Arkansas part of the Greenwood	
quadrangle		A 14 14 14 14 14 16 13 Command and developed	11 11
5. Estimated original reserves of coal in the Up	per Ha	s of coal in the Arkansas part of the Greenwood quadranglertshorne coal bed in the Arkansas part of the Greenwood	11
		1 1004	13
b. Description of selected wells drilled in or near	tne Gre	enwood quadrangle as of January 1, 1964	10

GEOLOGY OF THE ARKANSAS VALLEY COAL FIELD

GEOLOGY OF THE GREENWOOD QUADRANGLE, ARKANSAS-OKLAHOMA

By BOYD R. HALEY and THOMAS A. HENDRICKS

ABSTRACT

The Greenwood quadrangle is in west-central Arkansas and east-central Oklahoma, between lats 35°00′ and 35°15′ N. and longs 94°15′ and 94°30′ W. It comprises an area of about 184 square miles in Sebastian County, Ark., and about 60 square miles in Le-Flore County, Okla.

Sedimentary rocks of Middle Pennsylvanian age and unconsolidated sediments of Quaternary age are exposed at the surface, and sedimentary rocks of Late Cambrain to Middle Pennsylvanian age have been penetrated by wells drilled in or near the quadrangle.

The rocks in the quadrangle have been folded into eastward-trending synclines and anticlines and broken by normal and reverse faults. Displacement along one of the normal faults is probably 1,100 feet, and displacement along the reverse faults is estimated to aggregate more than 12,800 feet. Structural relief as measured on the base of the Hartshorne Sand-stone is more than 10,800 feet.

The Atoka, McAlester, and Savanna Formations contain coal beds. The Lower Hartshorne coal bed near the base of the McAlester Formation is the thickest, the most widespread, and the most important economically. The Upper Hartshorne coal bed, the only other economically important coal bed, is present only in the southern part of the quadrangle.

Commercial quantities of natural gas have been produced from the lower part of the McAlester Formation, the Hartshorne Sandstone, the Atoka Formation, the Morrow Series, the Penters Chert, and the St. Clair Limestone.

Building stone has been obtained from the Atoka, Hartshorne, and McAlester Formations. Road metal has been obtained from these formations, the Savanna Formation, and the gravelly part of alluvial deposits.

INTRODUCTION

This report on the geology of the Greenwood quadrangle is one of a series of reports being prepared by the U.S. Geological Survey in cooperation with the Arkansas Geological Commission. Its purpose is to (1) provide a geologic map of the quadrangle on a modern topographic base; (2) show the extent and thickness of all coal beds; (3) present estimates of coal reserve; (4) provide geologic data and interpretations pertinent to the location of natural gas and petroleum; (5) provide information about building stone, gravel, sand, and

clay; and (6) provide data on the nature and relations of the rock formations exposed at the surface and present in the subsurface.

This report is also published, under separate cover, as Arkansas Geological Commission Information Circular 20-F.

The Greenwood quadrangle is between lats 35°00′ and 35°15′ N. and longs 94°15′ and 94°30′ W. It covers an area of approximately 184 square miles in Sebastian County, Ark., and about 60 square miles in Le Flore County, Okla. (See fig. 1.)

Generalized geologic reports pertaining in part to the Greenwood quadrangle were made by Croneis (1930) and Haley (1960) for the Arkansas part, and by Drake (1897), Taff and Adams (1900), Taff (1905), Snider (1914), and Smith (1914) for the Oklahoma part.

Detailed geologic reports pertaining in part to the Greenwood quadrangle were made by Collier (1907) and Hendricks and Parks (1937, 1950) for the Arkansas part, and by Hendricks (1939) and Knechtel (1949) for the Oklahoma part.

The stratigraphic nomenclature and boundaries established by Hendricks and Parks (1950) for the Pennsylvanian rocks in the Fort Smith district, Arkansas, are used in this report with modifications. Merewether and Haley (1961) adopted Miser's (1954) terminology of McAlester, Savanna, and Boggy Formations, and Oakes' (1953) classification of the Krebs Group, which includes the Hartshorne Sandstone and the McAlester, Savanna, and Boggy Formations. Haley (1961) moved the contact between the Savanna Formation and the overlying Boggy Formation stratigraphically upward from that selected by most earlier workers, thereby conforming to Miser's (1954) interpretation. The pre-Pennsylvanian nomenclature used in this report conforms to that used in Arkansas. Table 1 compares the nomenclature used in the area of this report with that used in nearby areas.




FIGURE 1.—Location of report area (F, a) and areas of other published chapters of Arkansas Geological Commission
Information Circular 20 or of U.S. Geological Survey Professional Paper 536: A, Delaware quadrangle (Merewether and Haley, 1961); B, Paris quadrangle (Haley, 1961); C, Barber quadrangle (Haley, 1966); E, Knoxville quadrangle (Merewether, 1967); G and b, Scranton and New Blaine quadrangles (Haley, 1968); and H and c, Coal Hill, Hartman, and Clarksville quadrangles (Merewether and Haley, 1968).

STRATIGRAPHY

Rocks of Cambrian to Middle Pennsylvanian and of Quaternary age are exposed or have been penetrated by wells drilled in or near the quadrangle. The areal extent of some of these rocks is shown on plate 1, and the lithology of these rocks, except for those of quaternary age, is shown graphically on plate 2. All but two of the stratigraphic sections shown on plate 2 are described in detail. These two sections are the Shell Oil

Co. Western Coal and Mining Co. 1 (well 2, pl. 2), which was described by Haley and Frezon (1965), and the Nichols Exploration Corp. Gann 1 (well 12, pl. 2), which has been described by Haley (1966).

CAMBRIAN SYSTEM

Rocks of the Cambrian System were penetrated in the Shell Oil Co. Western Coal and Mining Co. 1 (well 2). Haley and Frezon (1965) were uncertain whether these rocks correlate with Cambrian rocks exposed to the north in Missouri or to the southwest in Oklahoma. They stated that "the lower 20 feet of this well penetrated rocks possibly equivalent to the upper part of the Derby-Doerun" in Missouri "and the Butterly Dolomite" in Oklahoma. "If this is so, there may be several hundred feet of sedimentary rocks between the total depth of this well and the Precambrian basement."

The above well penetrated 416 feet (depth of 10,508–10,924 ft) of very light to medium-gray granular to coarsely crystalline dolomite containing fine to coarse quartz sand and white to medium-light-gray opaque chert. Thin beds of sandstone are in the intervals 10,508–10,558 feet and 10,883–10,905 feet. The rock in the interval 10,905–10,924 feet consists of a dark-gray dolomitic silt-size quartz matrix containing very fine to medium quartz sand, very fine angular to subrounded crystals of feldspar, and abundant coarse crystals of light- to dark-gray and pink dolomite.

ORDOVICIAN SYSTEM

VAN BUREN FORMATION AND GASCONADE DOLOMITE UNDIFFERENTIATED

The Van Buren Formation and Gasconade Dolomite undifferentiated is 483 feet thick where penetrated by the Shell Oil Co. Western Coal and Mining Co. (well 2). The basal part of this unit is the Gunter Sandstone Member of the Van Buren Formation. The Gunter consists of 143 feet of fine to very coarse grained quartz sandstone. Thin beds of very light to medium-light-gray granular to medium-crystalline dolomite are in the lower 50 feet of the Gunter. The remainder of the Van Buren and Gasconade unit is very light to dark-gray granular to coarsely crystalline dolomite with scattered fine to coarse quartz sand and abundant white to light-gray or pink chert. Much of the white chert contains fine to medium dolomite rhombs. A few thin beds of dark-gray shale are in the upper 15 feet of the unit.

ROUBIDOUX FORMATION

The Roubidoux Formation is 230 feet thick where penetrated by well 2. It consists of very light to medium-light-gray granular to coarsely crystalline dolomite containing abundant fine to coarse quartz sand and white to medium-gray, olive-gray, or pink sandy and oolitic chert. Some chert is very light gray (milky) and some is medium gray (smoky). White chert containing very coarse crystals of dolomite is in the lower 75 feet of the formation.

JEFFERSON CITY DOLOMITE

The Jefferson City Dolomite is 465 feet thick where penetrated by well 2. It is predominantly light- to medium-dark-gray granular to medium-crystalline dolomite containing fine to coarse quartz sand and white, gray, or pink chert. Thin beds of dark-gray or grayish-black chert are scattered throughout the formation.

COTTER DOLOMITE

The Cotter Dolomite is 365 feet thick where penetrated by well 2. It is light- to dark-gray granular to finely crystalline dolomite containing light-gray or pink chert and some fine to coarse quartz sand. In the lower 60 feet of the formation some of the chert is oolitic and contains fine to medium quartz sand. A thin bed of greenish-gray pyritic shale is at the top of the formation.

POWELL DOLOMITE

The Powell Dolomite is 227 feet thick where penetrated by well 2. It is a light- to dark-gray granular dolomite containing widely scattered pyrite, some grayish-black chert, and some olive-gray translucent chert.

EVERTON FORMATION

The Everton Formation is 503 feet thick where penetrated by well 2 and probably at least 114 feet thick where penetrated by the Midwest Oil Corp. Floyd Morris 1 (well 9). The formation consists of medium- to dark-gray granular to finely crystalline dolomite containing fine to medium quartz sand and white to very light gray fine- to coarse-grained sandstone. Some dark-gray shale is in the upper and lower parts of the formation, and some medium-dark-gray and olive-gray dense to very finely crystalline limestone is in the middle of the formation.

ST. PETER SANDSTONE

The St. Peter Sandstone is 72 feet thick in well 2 and 81 feet thick, as estimated from the electrical log, in well 9. The formation is white to very light gray subrounded fine- to coarse-grained sandstone.

JOACHIM DOLOMITE

The Joachim Dolomite is 95 feet thick in well 2 and is estimated to be 83 feet thick in well 9; 141 feet of the formation was penetrated by Mobil Oil Co. W. K. Veazey 1 (well 18). The formation is mostly medium-to dark-gray granular to very finely crystalline dolomite containing fine to coarse quartz sand. Some beds of white to light-gray fine- to medium -grained sandstone are present. The upper 45 feet of the formation in the Veazey well (well 18) is light- to dark-gray very finely crystalline dolomite that is free of sand.

Table 1.—Stratigraphic nomenclature in or near the Greenwood quadrangle

		Ī	-		-												
West-central Arkansas (Hendricks and Parks, 1950)	Boggy Shale	Savanna Sandstone	McAlester Shale		Hartshorne Sandstone	Atoka Formation											
H.H.			S			CARBON											
East-central Oklahoma (Knechtel, 1949)	Boggy Formation	Savanna Formation	McAlester Formation	Upper	Sandstone Lower	Atoka Formation											
						PENNSYLVANIA Des Moines Seri											
East-central Oklahoma (Hendricks, 1939)	Boggy Shale	Savanna Sandstone	McAlester Shale	Upper Hartshorne	Lower	Atoka Formation											
						nsylvanian Series											
Generalized northeast and	Boggy Formation	Savanna Formation	McAlester Formation		Sandstone	Atoka Formation	Bloyd Kessler Limestone Formation Brentwood Limestone Member	Prairie Grove Hale Formation Cane Hill Member	Pitkin Limestone	Fayetteville Shale	Hindsville Limestone	Moorefield Formation	Boone Formation	Chattanooga Shale	Su	Sallisaw Formation	Frisco Limestone
		ss Series Group				Atoka Series	səirə2 v	Morrov	çe	ester ag	СР	leramec age	M sage age	Kinderhook age	Upper	Middle 7	Lower
		. 5			N	PENNSYLVANIA	T-1				N	MAISSIS	SIW			AINO	DEA
This report	Boggy Formation	Savanna Formation		McAlester Formation	Hartshorne Sandstone	Zone W Atoka Formation Zone P	Bloyd Kessler(?) Limestone Formation	Frairie Grove Hale Formation Cane Hill Member	Pitkin Limestone		Pre-Pitkin	post-Chattanooga formations		Chattanooga Shale		Penters Chert	
1			eder.			Atoka Series	Series	Morrow		er	ddU bns	Lower a		Kinderhook age		r or	Lower Midd
1	s	es Serie	Moine	səŒ			1							1 1 1.21	<u>L</u> !		

St. Clair Limestone and undifferentiated rocks	Sylvan Shale	Fernvale Limestone	Fite Limestone		McLish Formation	Tyner Formation	Powell Dolomite	Cotter Dolomite					
	190	ldΩ						voJ vobrO	•				
SILURIAN				ICIVN	оврои		-1		•				
St. Clair Limestone and undifferentiated rocks	Cason Shale	Fernvale Limestone	Plattin Limestone	Joachim Dolomite	St. Peter Sandstone	Everton Formation	Powell Dolomite	Cotter Dolomite	Jefferson City Dolomite	Roubidoux Formation	Gasconade Dolomite and Van Buren Formation undifferentiated	Gunter Sandstone Member	Dolomite
	190	ηqU		aldle	!W	1			1	19wor]	[Upper
SILURIAN ÷						N	OVICIA	овг					CYMBRIAN

313-705-68---2

PLATTIN LIMESTONE

The Plattin Limestone is 48 feet thick in well 2, 130 feet thick in well 9, and 125 feet thick in well 18. It is predominantly medium- to dark-gray dense to granular limestone containing abundant fine to coarse crystals of dolomite and calcite. Some beds of medium-light-gray and olive-gray very finely crystalline limy dolomite are in the lower part of the formation.

FERNVALE LIMESTONE

The Fernvale Limestone is 45 feet thick in well 2, 47 feet thick in well 9, and 48 feet thick in well 18. It is light- to medium-gray granular to coarsely crystalline limestone. Crystals of dolomite and pink calcite are rare to common.

CASON SHALE

The Cason Shale is 15 feet thick in well 2, 25 feet thick in well 9, and 22 feet thick in well 18. The formation is greenish-gray and dark-gray dolomitic shale that contains finely crystalline pyrite in some parts.

SILURIAN AND DEVONIAN SYSTEMS, ST. CLAIR LIMESTONE AND UNDIFFERENTIATED ROCKS

The St. Clair Limestone of this report is the St. Clair equivalent of Haley and Frezon (1965). It is 115 feet thick in well 2, 145 feet thick in well 9, and 52 feet thick in well 18. It grades from very light gray granular limy dolomite in well 2 through interbedded very light to medium-gray granular to very finely crystalline limy dolomite and light-gray granular to medium-crystalline dolomitic limestone in well 9 to medium-gray granular to finely crystalline dolomitic limestone in well 18. In wells 2 and 9 the St. Clair is overlain by the Penters Chert of Devonian age, and the Penters is overlain by the Chattanooga Shale of Devonian and Mississippian age. In well 18 the St. Clair is overlain by Chattanooga. In this well, about 100 feet of St. Clair and all of the Penters is missing because of normal faulting or, more probably, because of pre-Chattanooga post-Penters erosion.

The rocks identified as St. Clair Limestone in this report are in the interval of the Brassfield, St. Clair, and Lafferty Limestones of northwestern Arkansas, the Frisco and St. Clair Limestones of northeastern Oklahoma, and the Chimneyhill, Henryhouse, Haragan, and Bois d'Arc Limestones of south-central Oklahoma. These formations could not be identified with certainty in wells 2, 9, and 18.

DEVONIAN SYSTEM, PENTERS CHERT

The Penters Chert is 39 feet thick in well 2, about 25 feet thick in well 9, and absent in well 18. It is pre-

dominantly very light gray translucent chert or very light to medium-gray opaque chert with a few thin beds of very light to medium-gray granular limestone. The chert is limy, dolmitic, and pyritic. The formation is missing in well 18 because of normal faulting or pre-Chattanooga post-Penters erosion.

DEVONIAN AND MISSISSIPPIAN SYSTEMS, CHATTANOOGA SHALE

The Chattanooga Shale is 38 feet thick in well 2, 91 feet thick in well 9, and 35 feet thick in well 18. It is pyritic dark-gray to grayish-black shale.

MISSISSIPPIAN SYSTEM

POST-CHATTANOOGA PRE-PITKIN FORMATIONS

Rock units, or their equivalents, in this interval elsewhere in the Arkansas Valley and Ozark Mountains are, in ascending order, the Boone Formation, the Moorefield Formation, the Ruddell Shale, the Batesville Sandstone, and the Fayetteville Shale. This sequence of rocks is 368 feet thick in well 2, 257 feet thick in well 9, and 410 feet thick in well 18. The rocks consist of dark-gray granular to very finely crystalline silty limestone and dark-gray to grayish-black nonsilty to very silty nonlimy to very limy shale in wells 2 and 9, and of dark-gray shale, some of which is silty, some medium-gray limy siltstone, some dark-gray to grayish-black shale, and some medium- to dark-gray argillaceous granular silty limestone in well 18. The Boone Formation, which consists of limestone and chert north of the Greenwood quadrangle, cannot be recognized in wells 2, 9, and 18, but rocks equivalent to the Boone may be in these wells. The Ruddell Shale cannot be identified in wells 2, 9, and 18, but it or its equivalent may be present. In areas where the Batesville Sandstone is missing or unidentifiable, as it is in this quadrangle, the Moorefield Formation is distinguished lithologically from the Fayetteville Shale by the presence of silt in the shale and limestone of the Moorefield. Haley and Frezon (1965) used this criterion to separate the two formations, and their division is on plate 2 (well 2). If only the Moorefield contains silt, there is no Fayetteville in well 9, and only 35 feet of shale could be Fayetteville in well 18. A thin or missing Fayetteville can be explained by nondeposition, by postdepositional erosion, or by a facies change from typical Fayetteville nonsilty shale and limestone to nontypical Fayetteville, typical Moorefield silty shale, silty limestone, and siltstone. The authors believe that rocks equivalent to the Fayetteville are in well 9 but cannot be differentiated from the underlying rocks of the Moorefield. It seems reasonable to believe that the Fayetteville and equivalent rocks are more than 73 feet

thick in well 2 and more than 35 feet thick in well 18. (See pl. 2.)

PITKIN LIMESTONE

The Pitkin Limestone is 172 feet thick in well 2, 130 feet thick in well 9, and 124 feet thick in well 18. It is predominantly medium- to dark-gray dense to very finely crystalline limestone that contains abundant medium- to dark-gray oolites and, in places, very fine sand. Thin beds of dark-gray to grayish-black shale are present.

PENNSYLVANIAN SYSTEM

MORROW SERIES

The Morrow Series includes the Hale Formation and the overlying Bloyd Formation. These rocks are 438 feet thick in well 2 and 555 feet thick in well 9. Only the lowermost 97 feet of these rocks are in well 18; about 500 feet of the overlying rocks are missing because of a normal fault. (See pl. 4.) Haley and Frezon (1965) divided the Morrow Series into formations and members. Their division of the Morrow in well 2 is shown on plate 2. The Morrow rocks penetrated by well 9 cannot be divided with certainty and are shown on plates 2 and 4 as Bloyd and Hale. The rocks in the Morrow Series are predominantly dark-gray to grayish-black shale and medium-gray dense to finely crystalline limestone. Some light- to medium-gray very fine to mediumgrained sandstone and medium-gray siltstone are in the lower part.

ATOKA SERIES, ATOKA FORMATION

The Atoka Formation composes the Atoka Series in Arkansas and Oklahoma. It is 6,390 feet thick in well 2, about 7,943 feet thick in well 9, and 10,600 feet thick in well 18. The lower 600 feet of the Atoka is missing from well 18 because of a normal fault that was active during early and middle Atoka deposition. The Atoka ranges in thickness from about 5,500 feet in the northwestern part of the quadrangle (fig. 2) to about 14,750 feet in the southeastern part. The Atoka thickens southward; the middle and lower parts thicken more than the upper part. The fault plane cut by well 18 does not reach the surface in the Greenwood quadrangle. The amount of movement (about 1,100 ft) along this fault plane is thought to be compensated by an equal amount of concurrent thickening within the Atoka on the south side of the fault. However, if the fault formed in the late early or middle Atoka time, the upthrown side may have been eroded before the deposition of younger Atoka beds. Most, if not all, of this thickening could have occurred in the middle part of the formation. The Atoka Formation is mostly dark-gray to grayish-black shale that is slightly silty or silty in part, with lesser amounts of light- to medium-gray siltstone and light- to medium-gray slightly silty to silty very to fine to fine-grained sandstone that contains medium to coarse quartz sand in some places. Two beds of bentonitic shale are near the base of the formation in well 2, and one bed is in well 9.

Haley (1966) reported that parts of the Atoka Formation have lithologic characteristics that tend to set them apart. He designated the lower one "zone P" and the upper one "zone W." Zone P is near the middle of the formation and is distinctive because (1) the sandstone in it is coarser grained than most of the rest of the sandstone in the Atoka, (2) coarse-sand-size to granule-size quartz is common, and (3) some of the sandstone is limy and fossiliferous. Zone P is partly exposed on the north side of Backbone anticline at the spillway of Wofford Lake (pl. 1) and has been completely penetrated by wells 2, 9, and 18 and partly penetrated by well 12. (See pl. 2.) Zone W is in the upper one-third of the Atoka and is distinctive because it is a zone more than 400 feet thick that is mostly sandstone and siltstone with a small amount of shale. Zone W crops out along Washburn anticline in the east-central part of the Greenwood quadrangle and along Backbone anticline in the northern part of the quadrangle (pl. 1); it has been penetrated by wells, 2, 9, 12, 13, and 18 (pl. 2).

DES MOINES SERIES, KREBS GROUP

Hartshorne Sandstone.—The Hartshorne Sandstone unconformably overlies the Atoka Formation. The contact is well exposed in the roadcut near Hackett and in a roadcut south of Huntington along U.S. Highway 71 near the center of NE1/4SW1/4 sec. 25, T. 5 N., R. 31 W. The Hartshorne Sandstone ranges in thickness from 10 to 210 feet in the Greenwood quadrangle. It is predominantly very light to medium-gray very fine to fine-grained sandstone that is slightly silty or silty in part. Thick beds of shale and and siltstone in the formation crop out along the south side of the Backbone anticline. (See pl. 1.) The sandstone is in beds of the channel type throughout much of the Greenwood quadrangle. The channel-type sandstone is well exposed in the roadcut along Arkansas State Highway 45 near the NW cor. NE1/4NE1/4 sec. 21, T. 6 N., R. 32 W., and in the quarry near the center of NE1/4SW1/4 sec. 35, T. 7 N., R. 31 W. At the quarry about 2 feet of one channel is filled with angular fragments of dark-gray shale as large as 3 by 15 by 20 inches and ironstone concretions as large as 3 by 6 by 10 inches.




FIGURE 2.—Thickness of Atoka Formation in the Greenwood quadrangle (shaded) and vicinity, Arkansas and Oklahoma. Interval is 1,000 feet. Thickness lines from Haley (1961, fig. 6; 1966, fig. 3) with modifications based on subsequent information.

McAlester Formation.—The McAlester Formation conformably overlies the Hartshorne Sandstone. It is 1,458 feet thick in the Veazey well (No. 18). Hendricks (1939) estimated thicknesses of 1,850 feet at one location (pl. 33) and 2,000 + feet at another location (fig. 15) on the basis of scattered surface measurements across many concealed intervals. The McAlester Formation is dark-gray to grayish-black shale with minor amounts of medium-gray siltstone and light- to mediumgray very silty very fine grained sandstone to light-gray very fine grained sandstone. The McAlester has at least four coal beds; the most economically important and widespread is the Lower Hartshorne coal bed near the base of the formation. Excellent sediment-flow features are exposed in NW1/4NW1/4 sec. 2, T. 4 N., R. 32 W. The McAlester Formation of this report contains rocks considered by Hendricks and Parks (1937) to be equivalent of the upper part of the Hartshorne Sandstone in Oklahoma. These rocks are the shale below the Hartshorne coal, the Hartshorne coal, the shale above the coal, and the lenticular sandstone above the shale. These rocks cannot be mapped northeast of sec. 24, T. 6 N.,

R. 31 W. (pl. 1), so Hendricks and Parks and the authors of this report used the top of the first sandstone below the Lower Hartshorne coal bed as the base of the McAlester.

Savanna Formation.—The Savanna Formation overlies the McAlester with a locally unconformable contact. However, at places the contact is gradational and the McAlester and Savanna intertongue. The Savanna Formation is 1,300 feet thick in the Greenwood quadrangle. It is medium- to dark-gray shale with smaller amounts of light- to medium-gray siltstone and light-to medium-gray very silty very fine grained sandstone. Sediment-flow features are common in the sandstone.

Boggy Formation.—The Boggy Formation overlies the Savanna conformably. It is represented by 25 feet of very light gray very fine to medium-grained friable quartzose sandstone on Sugarloaf Mountain. Hendricks (1939, p. 272) reported as much as 4,000 feet of Boggy in nearby areas, but Miser (1954) revised the base of the Boggy and included beds in the Savanna that Hendricks placed in the Boggy.

QUATERNARY SYSTEM

TERRACE DEPOSITS

Alluvial material deposited by the Arkansas River forms one terrace in the northwest corner of the Greenwood quadrangle, and alluvial material deposited by local streams forms one or two terraces everywhere in the quadrangle. Terrace deposits along the Arkansas River consist of clay, silt, and sand, some of which is of local origin; pebbles and cobbles of shale and sandstone of local origin; and pebbles of quartz and chert of distant origin. The terrace deposits formed by local streams consist of clay, silt, and sand, and pebbles, cobbles, and boulders of shale, siltstone, and sandstone of local origin. Reworked material from the river terrace is in some of the stream terraces. The river-terrace gravel and the uppermost stream-terrace gravel are thought to be equivalent to the Gerty Sand of Pleistocene age.

ALLUVIUM

Alluvium has been deposited along most of the streams in the Greenwood quadrangle. It consists of clay, silt, and sand, pebbles of shale, siltstone, and sandstone, and, in some places, cobbles and boulders of shale, siltstone, and sandstone. Some of the alluvium contains reworked material from the river terrace.

STRUCTURE

The Greenwood quadrangle is in the Arkansas Valley section of the Ouachita province (fig. 1). The rocks in the quadrangle have been folded into east-trending anticlines and synclines. Two anticlines have been broken by reverse faulting and one syncline has been broken in one place by normal faulting. (See pls. 1, 3.) Structural relief on the base of the Hartshorne Sandstone is more than 10,800 feet as measured from the trough of the Cavanal syncline to the projected crest of the Backbone anticline. (See pls. 3, 4.)

The closure of the anticlines is thought to diminish with depth partly because of the southward-thickening of the Atoka Formation and partly because folds in near-surface rocks are represented by reverse faults at depth that cut the bedding of the rocks at an angle that decreases downward until the movement becomes bedding-plane slippage.

The south limb of the Central syncline extends across the northern part of the quadrangle; the Jenny Lind syncline extends across the extreme northeast corner of the quadrangle; the Greenwood syncline extends across the north-central part of the quadrangle; the Cavanal syncline extends across the south-central part of the quadrangle; and a part of the north limb of the Poteau Mountain syncline extends across the southeast corner of the quadrangle.

The faulted Backbone anticline extends across the northern part of the quadrangle; the Washburn anticline extends westward into the northeastern part of the quarangle; the Midland anticline extends eastward nearly across the quadrangle; and the Hartford anticline extends across the southeast corner of the quadrangle. The Backbone anticline has been broken by reverse faulting throughout most of its extent in the Greenwood quadrangle. The Washburn anticline has been broken by reverse faulting in the extreme eastern part of the quadrangle. The south limbs of the unfaulted Midland and Hartford anticlines are steeper than the north limbs, whereas the north limbs of the Backbone and Washburn anticlines are steeper than the south limbs.

The normal faults at the surface in the west-central part of the quadrangle (pls. 1, 3) have displacements of less than 40 feet. One of the faults dips 46° S. where exposed in sec. 28, T. 8 N., R. 27 E., but it dips an estimated 60° S. in sec. 5, T. 5 N., R. 32 W. A normal fault with a displacement of about 1,100 feet is at a depth of 12,815 feet in the Veazey well (well 18). This fault does not extend to the surface, and how much of the Atoka, or younger formations, is cut by this fault is unknown. The strike and the direction and amount of dip of the fault plane are unknown, but elsewhere in Arkansas, normal faults of this magnitude generally strike east and dip southward at angles of 50°-60°. (See section B-B', pl. 4.) Three normal faults were discovered by coal miners in the northeastern part of the quadrangle. The direction of dip of the fault plane was recorded for two of these faults, and a dip of 63° N. was recorded for the fault in sec. 31, T. 7 N., R. 32 W. The amount of displacement along these faults is unknown but probably is less than 15 feet.

The reverse faults in and near the Greenwood quadrangle are in zones that may contain as many as 12 reverse faults and be as much as 2 miles wide. (See pl. 1, see also Haley, 1966, pl. 1.) Movement along the reverse faults probably represents a relief of the pressure that caused the folding of the Backbone and Washburn anticlines.

A small segment of one fault in the Washburn fault zone is in sec. 24, T. 6 N., R. 31 W. The movement along the Washburn fault zone decreases from 5,000+ feet as measured on zone P in T. 6 N., R. 27 W. (Haley, 1966, p. 11), to zero on the west end of the fault in the Greenwood quadrangle.

The Backbone fault zone, which extends nearly across the northern part of the Greenwood quadrangle, consists of two to five faults and is 300–4,000 feet wide. The fault planes of the major faults in the Backbone zone probably dip southward from angles near vertical

at the surface to less than 15° in the subsurface. Fault planes of the major faults are not exposed in the quadrangle; however, they can be accurately mapped, and a dip of 75° can be estimated for the fault in NW1/4 sec. 2, T. 6 N., R. 31 W. The major fault planes have angular relationships to the strata; these range from parallel to nearly 90° in the oversheet and from parallel to nearly 180° in the undersheet, where the strata are overturned. The amount of movement along any one fault is unknown, but the combined amount of movement along all the faults, as estimated on the projected base of the Hartshorne Sandstone, exceeds 12,800 feet near the Arkansas-Oklahoma boundary. The apparent amount of movement along these fault planes and along the fault zone decreases to zero at that place in the subsurface where the fault planes become parallel to bedding planes of the encompassing rocks. Slickensided shale, siltstone, and sandstone, found along many of the major faults, are well exposed in the quarry in NE1/4SE1/4 sec. 4, T. 6 N., R. 32 W.

The subsidiary reverse faults in the quadrangle have smaller magnitude and less steeply dipping fault planes. Fault planes of some of these faults are exposed in the following places: In a roadcut on Arkansas State Highway 45 in the center of NE½SW½ sec. 4, T. 6 N., R. 32 W., where the dip is 55° S. and the amount of displacement is probably less than 10 feet; near the center of NW½SW½ sec. 4, T. 6 N., R. 32 W., where the dip is 10° S. and the amount of displacement could be as much as 800 feet; and near the center of NE½NE½NW½ sec. 2, T. 6 N., R. 32 W., where the dip is 35° S. and the amount of displacement could be as much as 1,600 feet.

A north-dipping reverse fault is exposed in the roadcut of U.S. Highway 71 in SE¼SE¼SE¼ sec. 31, T. 7 N., R. 31 W., where the dip of the fault plane ranges from 5°-15°. The amount of southward movement along this fault is unknown but is probably small.

ECONOMIC GEOLOGY

COAL

The Atoka, McAlester, and Savanna Formations contain coal beds. The Lower Hartshorne coal bed has been mined rather extensively in the area, and the Upper Hartshorne and the Stigler coal beds have been mined locally. The extent, thickness, and mined area of the Lower Hartshorne coal bed are shown on plate 3. The outcrops of all other coal beds are shown on plate 3, and the thickness measurements for these coal beds are listed in table 2.

Table 2.—Selected coal thickness measurements in the Greenwood quadrangle

[All measurements made in the Upper Hartshorne coal bed in the McAlester Formation, except as noted]

Approximate location	Depth of coal (feet)	Thickness of coal (inches)
Arkansas		
T. 6 N., R. 31 W. Center NE¼SE¼ sec. 36 ¹ T. 6 N., R. 38 W.	Outcrop	4
T KN D et IV	58	2
SW cor. NE 1/NE 1/2 sec. 7? NE cor. SE 1/NW 1/NW 1/2 sec. 28. NW cor. SW 1/NW 1/2 sec. 28. SW cor. SE 1/SE 1/NW 1/2 sec. 28. SE cor. NW 1/NW 1/2 sec. 28.	13 59 64 78 108	12 14 16 15 8
8E cor. NW48W4 sec. 28. SE cor. NE4NE4NE48W4 sec. 28. SW cor. SW4 sec. 28. SE cor. SW4NW48E48W4 sec. 28. Center NW48E48W4 sec. 28.	140 67 166 138 102	24 18 4 24 15
SW cor. SE1/SE1/SW1/4 sec. 28 SE cor. NW1/SE1/4 sec. 28. SW cor. SE1/NE1/SE1/4 sec. 28. SW cor. SE1/SE1/SE1/4 sec. 31. Center NE1/ANE1/ANE1/4 sec. 32.	81 37 23 64 230	8 18 22 10 24
NW cor. NE¼NW¼NE¼NE¼ sec. 32 Center NW¼NE¼SW¼ sec. 32 Center SE¼NE¼SW¼SE¼ sec. 32 NE cor. NW¼NE¼ sec. 33 SE cor. NW¼NE¼ sec. 33	238 192 80 50 12	24 24 10 30 24
SW cor, NW\\SW\\\ANE\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	33 128 174 88 33	7 18 9 24 7
T. 5 N., R. 32 W.		
N W cor. SW/4SE 1/4 sec. 11 Center SE 1/4 SE 1/4 sec. 11 Center SW/5W 1/4 sec. 12 Center NE 1/4 NE 1/4 sec. 14 Center NW 1/4 NE 1/4 sec. 14 Center SW 1/4 NW 1/4 sec. 14 Center SW 1/4 NW 1/4 sec. 14 Center SE 1/4 SE 1/4 Sec. 14 Center SE 1/4 SE 1/4 Sec. 21 1 Do	186 148 138 111 132 126 192 343 700	31 52 66 54 70 33 39 24
NW cor. 8W¼8W¼8E¼NE¼ sec. 28 ³. D0.3. D0.5. D0.2. D0.4. D0.5. D0.5. SW cor. SE¼8W¼NE¼ sec. 29 4	79 187 200 819 845 1,200 1,505 Outcrop	6 6 18 4 12 12 11 4
T. 4 N., R. 52 W.	24	9
900 ft from north line, 2,300 ft from west line sec. 2 \$	408 780 1, 182	12 12 5
2,050 ft from north line, 1,700 ft from west line sec. 6 5	Outcrop 241 626 1,058	4 4 3 9
NE cor. SE¼SE¼NW¼ sec. 8 2	303 727	2
Center sec. 9. SW cor. NW1/NW1/SE1/SE1/ sec. 9. SW cor. SW1/NW1/SE1/SE1/ sec. 9.	44 26 45	18 4 6
Center NW\\\SW\\\\SE\\\\\\\\\\\\\\\\\\\\\\\\\\\	38 34 31 231 256	6 8 15 18 26
NW cor. 8W¼8W¼ sec. 16 NW cor. 8W¼8W¼8W¼ sec. 19 Center NW¼8W¼8W¼ sec. 19. Center NW¼NE¼ sec. 23 Do.³	280 307 275 231 252	30 8 32 5 3

See footnotes at end of table.

Table 2.—Selected coal thickness measurements in the Greenwood quadrangle-Continued

Approximate location	Depth of coal (feet)	Thickness of coal (inches)
Oklahoma		
T.7 N., R. 27 E. SW cor. sec. 5 4 Center SE4/NE4/NW4/ sec. 29 4 SW cor. SW4/SE4/NE4/SW4/ sec. 29 4	Outerop Outerop Outerop	16 16 16

- Unnamed coal bed in Atoka Formation.
 Unnamed coal bed in McAlester Formation.
 McAlester (?) coal bed in McAlester Formation.
 Stigler coal bed in McAlester Formation.
 Charleston (?) coal bed in Savanna Formation.

All coal in the Greenwood quadrangle is classified as low-volatile bituminous (Haley, 1960, pl. 62; Trumbull, 1957, pl. 17) on the basis of the percentage of dry mineral-matter-free fixed carbon in the coal, in accordance with the specifications of the American Society for Testing and Materials (1939).

The estimated reserves of coal listed in tables 3 and 5 are tabulated in categories of amount of overburden, thickness of coal, and abundance of reliable thickness data in accordance with the standards and procedures adopted by the U.S. Geological Survey (Averitt, 1961, p. 14-26). The original, remaining, and recoverable reserves of coal listed in table 4 are also categories conformable to those of Averitt.

Trumbull (1967, p. 341-345, and pl. 17) described the rank, thickness, thickness of overburden, amount of reliable thickness data, and mined areas of the Lower Hartshorne coal bed in the Oklahoma part of the Greenwood quadrangle, but the amount of coal estimated to be in this area cannot be determined from his report. The coal-bearing part of this area is about onehalf as large as the coal-bearing part of the quadrangle in Arkansas, and the coal has about the same average thickness; therefore, it seems reasonable to believe that this area contained as much as 140 million short tons of coal prior to mining.

Coal beds in the Atoka Formation

An Atoka coal bed crops out in the Greenwood quadrangle along the county road in NE1/4SE1/4 sec. 36, T. 6 N., R. 31 W. This coal bed, near the top of zone W, is known to extend eastward from the quadrangle for more than 45 miles. A coal bed was penetrated by the Gann well (well 12) at a depth of 438 feet. This coal bed was not found at the surface in the Greenwood quadrangle; however, it was found in the quadrangle to the east (Haley, 1966, pl. 1).

Coal beds in the McAlester Formation

Four McAlester coal beds are known in the Greenwood quadrangle. They are, in ascending order, the Lower Hartshorne coal bed, near the base; the Upper Hartshorne coal bed, 60-90 feet above the Lower Hartshorne coal bed; the McAlester coal bed, near the middle of the formation; and the Stigler coal bed, near the top of the formation.

The Lower Hartshorne coal bed is the thickest, most widespread, and most important economically in the Greenwood quadrangle. It lies near the base of the McAlester Formation, and in some areas the "bed" is actually a zone of 1-7 beds. The thickness of the coal, the amount of overburden, the mined areas, and the outcrop of the Hartshorne coal bed are shown on plate 3. The estimated reserves of coal in the Lower Hartshorne coal bed in the Arkansas part of the quadrangle after mining are listed in table 3, and the estimated original reserves, the estimated amount of coal mined and lost in mining, and the estimated recoverable reserves of coal in the Lower Hartshorne coal bed in the same area are listed in table 4.

Table 3.—Estimated remaining reserves of coal in the Lower Hartshorne coal bed in the Arkansas part of the Greenwood quadrangle [In millions of short tons]

Organization (fact)	$\mathbf{T}\mathbf{h}$	ickness of o	coal (inch	es)
Overburden (feet)	14-28	28-42	>42 48. 645 6. 338	Total
Measured an	d indicated rese	rves		
0-1,000 1,000-2,000 2,000-3,000	3. 638	50.275 2.487	6. 338	102. 558 8. 825
Total	3. 638	52. 762	54. 983	111. 383
Inferi	red reserves			
0-1,000 1,000-2,000 2,000-3,000	243	45. 560 24. 092 6. 017	13. 561	61, 691 37, 896 7, 768
Total	5. 006	75. 669	26. 680	107. 355
Tota	al reserves			
0-1,000 1,000-2,000 2,000-3,000	243	95. 835 26. 579 6. 017	19.899	164. 249 46. 721 7. 768
Total	8. 644	128. 431	81.663	218. 738

Table 4.—Estimated original, remaining, and recoverable reserves of coal in the Arkansas part of the Greenwood quadrangle

Į.	in millions (of short tons		
Coal bed	Original reserves	Amount of coal mined and lost in mining	Remaining reserves	Recoverable reserves
Lower HartshorneUpper Hartshorne	315. 552 28. 004	96. 814	218. 738 28. 004	109.369 14.002
Total	343. 556	96. 814	246. 742	123. 371

The Upper Hartshorne coal bed, 60-90 feet above the Lower Hartshorne coal bed, is present only in the southern part of the quadrangle. The outcrop of the coal bed is shown on plates 1 and 3, and coal-bed thicknesses are listed in table 2. The estimated original reserves of Upper Hartshorne coal in the Arkansas part of the quadrangle listed in table 5 are modifications of those reported by Haley (1960, table 1, p. 806). The estimated amount of coal mined and lost in mining, the remaining reserves, and the recoverable reserves in the Upper Hartshorne coal bed in the same area are listed in table 4.

The McAlester coal bed, near the middle of the McAlester Formation, is present only in the southwestern part of the quadrangle. The outcrop of the coal bed is shown on plates 1 and 3, and the measured thicknesses are recorded in table 2. The reserves of coal in the McAlester coal bed were not estimated because the coal is thought to be less than 14 inches thick throughout its extent in the quadrangle.

The Stigler coal bed, near the top of the McAlester Formation, is known only in the southwestern part of the quadrangle. The outcrop of the coal bed is shown on plates 1 and 3, and the measured thicknesses are tabulated in table 2. Reserves of coal in the Stigler coal bed were not estimated.

Table 5.—Estimated original reserves of coal in the Upper Hartshorne coal bed in the Arkansas part of the Greenwood quadrangle

[In millions of short tons. Modified from Haley (1960, table 1, p. 806)]

O-subsurder (feet)	$\mathbf{T}\mathbf{h}$	ickness of	coal (inche	:8)
Overburden (feet)	14-28	reserves 417	>42	Total
Measured and	l indicated rese	rves		
0-1,000 1,000-2,000 2,000-3,000	-			
Total				
Inferr	ed reserves			
0-1, 000 . 1, 000-2, 000 . 2, 000-3, 000 .	15. 983 416			15. 983 . 416
Total	16. 399			16. 399
Tota	l reserves			
0-1, 000 . 1, 000-2, 000 . 2, 000-3, 000 .	27. 400 416	0.188		27. 588 . 416
Total	27. 816	. 188		28. 004

Coal beds in the Savanna Formation

One coal bed is known in the Savanna Formation in the Greenwood quadrangle, but it seems likely that others exist. The one known coal bed is 4 inches thick and is exposed near the base of the Savanna Formation in sec. 6, T. 4 N., R. 32 W. (pl. 1). This coal bed could be equivalent to the Charleston coal bed which is at this stratigraphic position elsewhere in Arkansas.

OIL AND GAS

Oil has not been discovered in the Greenwood quadrangle: however, streaks and blebs of solid carbonaceous material (dead oil) are present in the upper part of the St. Clair Limestone in well 9. The first producing gas well in Arkansas was drilled 11/2 miles east of the quadrangle on the Hartford anticline in 1902. This well, the Choctaw Oil and Gas Co. Duncan 2, is the discovery well for the Mansfield gas field. The discovery wells for three other gas fields in the Greenwood quadrangle are the Shell Oil Co. Western Coal and Mining Co. (well 2) in the Bonanza field (pl. 3), the Le Flore County Gas and Electric Co. Hill 1 drilled west of the report area in the Poteau-Gilmore field, and an unknown well in the Rock Island field. These wells and others drilled in or near the Greenwood quadrangle are described in table 6.

Gas in the Greenwood quadrangle has been produced from the St. Clair Limestone, the Penters Chert, the Morrow Series, the Atoka Formation, the Hartshorne Sandstone, and the lower part of the McAlester Formation. Gas in the Mansfield gas field has been produced from standstone units mostly in zone W (Haley, 1966, p. 20). Gas in the Bonanza gas field has been produced from the St. Clair Limestone, Penters Chert, lower part of the Morrow Series, and middle part of the Atoka Formation. The gas from the Poteau-Gilmore gas field comes from the Hartshorne Sandstone and from the lowermost sandstone in the McAlester Formation. Gas in the Rock Island gas field is from the upper one-third of the Atoka Formation.

Gas is found in many of the Morrow, Atoka, Hartshorne, and lower McAlester sandstone beds. The extent and volume of gas in these rocks is dependent upon structure and lithologic changes. The importance of lithologic entrapment is exemplified by wells 10, 11, 12, 14 (table 6), all of which produce or have shows of gas from rock units that crop out updip from the wells.

BUILDING STONE

Slabs and blocks of weathered sandstone from the Atoka Formation have been used on the exterior of many of the buildings in the area. Building stone has been quarried from the Hartshorne Sandstone in secs. 9 and 10, T. 8 N., R. 27 E.; sec. 20, T. 6 N., R. 32 W.; and sec. 35, T. 7 N., R. 31 W.; and from a sandstone in the McAlester Formation in sec. 4, T. 7 N., R. 27 E. Most of the Hartshorne Sandstone used in building is taken from long foreset beds of remarkably uniform thickness. It is a popular building stone because of its uni-

Table 6.—Description of selected wells drilled in or near the Greenwood quadrangle as of January 1, 1964

							*		1		
Well No. I-4)	Сотрапу пате	Lease name	Location (EL, east line; NL, or north line; BL, south line; WL, west line)	Total Red depth el	Reported eleva- E tion c (ft)	Electri- cal log	Stratigraphic zone of production	Depth of production p (ft)	Reported C production (cu ft per day)	Comple- tion date	Remarks
-	Shell Oil Co	Western Coal and Mining	339 ft north and 363 ft west of center sec. 31, T. 7 N., B. 31 W.	8, 030	484 7	Yes J	Prairie Grove MemberSt. Clair Limestone	7, 075-7, 085 7, 880-7, 890	3, 820, 000 1, 880, 000	June 1963	
C4	ор	Co. 3. Western Coal	620 ft south and 450 ft west of	10,924	505	do	Middle part, Atoka Forma-	2,985	20,000	Apr. 1962	Discovery well of Bonanza Field First commercial
		Co. 1.				34 -7 (1-1	St. Clair Limestone. Powell Dolomite. do Roubidoux Formation.	7, 936-7, 958 8, 802-8, 812 8, 924-8, 930 9, 857-9, 975	9, 400, 000 100, 000 70, 000 Show of gas.		production in Arkansas from rocks older than Devonian. Rock samples examined and logged by B. R. Haley to 7.400 ft and by S. F. Fregon
c	Ç	E Hamilton A-1	805 ft south and 330 ft wast of								from 7,400 to 10,924 ft. Described by Haley and Frezon (1965). Being drilled.
4	op	Western Coal	Western Coal 400 ft north and 500 ft east of	8, 057	1 518 Y	Yes h	Middle part, Atoka	4, 618-4, 638	700,000	Nov. 1962	
			CELLICE Sec. 30, 1.1 14, 15. 32 W.				Formation. Prairie Grove Member	7, -113-7, 120 7-740, 7, 874	275,000 21,000,000		
τ.	ор	Young 1-2	1,980 ft from SL and 1,980 ft from WL NWL NWK sec. 2, T. 6 N., R.	8, 150	582	op.	St. Clair Limestonedodo	7, 946-7, 958 7, 901-8, 045	2, 500, 000 5, 600, 000	June 1962	
9	op	Acee Milk Co. 1-3	32 W. 1,320 ft south and 1,980 ft west of	8,182	548	qo	Prairie Grove Member	7,230-7,290	3,800,000	Nov. 1963	
7	Le Flore County Gas and Electric	Tompas-Back- bone 1.	NE cor. sec. 3, 1, 6 N., K. 32 W. Center SW4/S W4/ sec. 31, T. 9 N., R. 27 E.	4,845	2 670		L'enters Chert		Z, swi, wo	1944	
œ	Co. do	McClure 1	Center NEWS WMN WM sec. 7,	2, 771	2 485 D	No.			Dry	1923	
O.	Midwest Oil Corp	F. Morris 1	1.5 Nr., K. 27 E. 3,300 ft from SL and 2,840 ft from WL sec. 12, T. 7 N., R. 26 E.	9,216	1476 3	Yes	Zone P, Atoka Formation	5, 205-5, 262	2, 000, 000	1961	Discovery well of deeper gas in Rock Island gas field. Well is 3,860 ft west of Greenwood
											quadrangie. Rock samples examined and logged by S. F. Frezon.
10	Le Flore County Gas and Electric	Littman 26	Center NEWN WWN W% sec. 18, T. 8 N., R. 27 E.	2,615	2 470 I	No	Upper part, Atoka Formation.		Gas 3	1922	400 ft west of Greenwood quadrangle.
11	Co.	Littman 25	Center S W N W N W Sec.	1,607	2 470	do	op		Gas 3	1922	700 ft west of Greenwood
12	J. W. Nichols Exploration Co.	Gann 1	Center NE. 31 W. 5 80. 15, T. 5 N., R. 31 W.	6, 005	565	Yes	ор		Dry	Sept. 1957	Gas escaping around casing in March 1958 (Haley, 1966, table 3). Rock samples ex- amined and logged by B. R.
5	Wheeler and Rvan	Sebastian County	2.210 ft from SL and 2.146 ft	6.016	563	op			Dry	April 1962	Haley. Described by Haley (1966). Rock samples examined and
;		Coal and Mining Co. 1.	from WL of sec. 14, T. 5 N., R. 32 W.	100			Tone W. Ateles Domestics		Ohour of man		logged by R. B. Haley.
14	Atheletic Mining and Smelting Co.		14, T. 5 N. R. 32 W.	4, 440	20 6		Zone W, Atoks formation	09° 'e	Dilow of gas	6001	
15	Le Flore County Gas and Electric Co.	F. L. Holton 29	34, T. 8 N., R. 27 E.	1,505		do	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			1923	
16	dodo	Mooneyahm 22 Kilgore-Cedars 5	Center SEMN WMN WM sec. 32, T. 8 N., R. 27 E. 5. Center N WMSEMNEM sec.	2, 487 3, 250	0692	qo qo			Gas *	1921	
	4		9, T. 7 N., R. 27 E.								
χè	See footnotes at end of table	table									

Table 6.—Description of selected wells drilled in or near the Greenwood quadrangle as of January 1, 1964—Continued

Remarks	Rock samples examined and logged by B. R. Haley to 13, 400 ft and by S. E. Frezon		1927 300 ft west of Greenwood guadrangle.			1914 2,900 ft south of Greenwood quadrangle.				
Comple- tion date	1962	1925	1927				1945	1922	1923	1914
Reported production (cu ft per day)	25,000	Gas 8	Gas 3	Gas ³	Gas f	2,210 Show of gas. 3,587 do	op.	950, 500 1, 391, 000 250, 000	1, 500, 000	2,005 1,700,000 1,180 Gas 3 2,200 Gas 4
Depth of production (ft)	. 5,494-5,510	Gas *		į		2,210 3,587 4,035	786- 799	1,240		
Stratigraphic zone of production	11,152 Yes Zone W, Atoka Formation 5,494-5,510		\$ 635do	2 620do			*610do Upper part, AtokaForma-	Zone W, Atoka Formation	do Upper part, Atoka Forma- tion. Zone W, Atoka Formation.	Upper part, Atoka Formation
Electri- cal log	Yes	No	op	op	2 655do	do029 8	qo	- qo	op 069 z	2 740do
eported eleva- tion (ft)	11,152	3 650 No.	1635	2 620	2 655	\$ 670	1 610	2 680	2 690	2 740
Total Reported depth eleva- (ft) (ft)	13, 871	1,478	1, 539	1, 596	2, 134	4,270	1,804	2,071	2,016	2,265
Location (EL, east line; NL, north line; SL, south line; WL, west line)	3, 630 ft from SL and 840 ft from WL sec. 28, T. 7 N., R. 27 E.	Center SEMNEMN WM 800.30, T. 7 N., R. 27 E.	Center SEKN WKN WK sec. 30, T. 7 N., R. 27 E.	Center SEXSWXN WX Sec. 30, T. 7 N., R. 27 E.	Center SEXS WKNEX Sec. 30,	4,200 ft from NL and 1,300 ft from EL sec. 21, T. 4 N., R. 32 W.	2,000 ft from NL and 1,450 ft from	4,000 ft from NL and 3,500 ft from WL sec. 2, T. 4 N., R. 31 W.	4,300 ft from NL and 2,600 ft from WL sec. 2, T. 4 N., R. 31 W.	5,050 ft from NL and 2,600 ft from WL 8ec. 2, T. 4 N., B. 31 W.
Lease name	W. K. Veazey 1	Garrett 55	Garrett 76	Slocum 78	Hall 56	Hartford 1	Tucker 1		6	. 10.
Сотрапу пате	18 Mobil Oil Co W. K. Veazey 1 3,630 ft from SL 8 WL 8ec. 28, T.	19 Le Flore County Gas and Electric	i	21do	22do	23 Central Coal and Coke Co.	24	25 Mansfield Gas Co 12.	26do	27do
Well No. [pls.	18	19	20 .	21	22	23	24 -	52	26 .	27 -

1 Elevation of derrick floor. 2 Elevation estimated. 3 Quantity unknown.

form thickness, pleasing light color and lamination, and resistance to weathering. Shale has been quarried as a clay source for brick from the Atoka Formation in the center of sec. 36, T. 5 N., R. 31 W.

ROAD METAL

Shale or interbedded shale and siltstone has been quarried for road metal from the Atoka and McAlester Formations, and sandstone has been quarried for road metal from the Hartshorne Sandstone. Gravel from the river terraces and clinker from burned coal-mine dumps have also been used as road metal.

GRAVEL, SAND, AND CLAY

The river terraces, some of the stream terraces, and most of the alluvium contain well-sorted gravel. Sand is present in much of the alluvium. A zone of weathered shale at least 6 feet thick is present underneath the stream terrace along Arkansas State Highway 45 in the SW1/4NW1/4 sec. 11, T. 4 N., R. 32 W. This weathered shale is similar to that used as a source of clay for brick elsewhere in Arkansas. Deposits of nonsandy or nonsilty clay are rare in the alluvium or terrace deposits.

REFERENCES CITED

- American Society for Testing and Materials, 1939, Standard specifications for classification of coals by rank (ASTM designation D 388-38), in 1939 Book of ASTM Standards, Pt. 3, Nonmetallic minerals—general: Philadelphia, p. 1-6.
- Averitt, Paul, 1961, Coal reserves of the United States—A progress report, January 1, 1960: U.S. Geol. Survey Bull. 1136, 116 p.
- Collier, A. J., 1907, The Arkansas coal field, with reports on the paleontology by David White and G. H. Girty: U.S. Geol. Survey Bull. 326, 158 p.
- Croneis, C. G., 1930, Geology of the Arkansas Paleozoic area, with special reference to oil and gas possibilities: Arkansas Geol. Survey Bull. 3, 457 p.
- Drake, N. F., 1897, A geological reconnaissance of the coal fields of the Indian Territory: Am. Philos. Soc. Proc., v. 36, no. 36, p. 326-419.
- Fenneman, N. M., and Johnson, D. W., 1946, Physical divisions of the United States: U.S. Geol. Survey Map (reprinted 1949).
- Haley, B. R., 1960, Coal resources of Arkansas, 1954: U.S. Geol. Survey Bull. 1072-P, p. 795-831.

- Haley, B. R., 1961, Geology of the Paris quadrangle, Logan County, Arkansas: Arkansas Geol. Comm. Inf. Circ. 20-B, 40 p.

- Haley, B. R., and Frezon, S. E., 1965, Geologic formations penetrated by the Shell Oil Company No. 1 Western Coal and Mining Co. well on the Backbone anticline, Sebastian County, Arkansas: Arkansas Geol. Comm. Inf. Circ. 20-D, 17 p.
- Hendricks, T. A., 1939, The Howe-Wilburton district, Latimer and Le Flore Counties, pt. 4 of Geology and fuel resources of the southern part of the Oklahoma coal field: U.S. Geol. Survey Bull. 874-D, p. 255-300.
- Hendricks, T. A., and Parks, Bryan, 1937, Geology and mineral resources of the western part of the Arkansas coal field: U.S. Geol. Survey Bull. 847-E, p. 189-224.
- ———— 1950, Geology of the Fort Smith district, Arkansas: U.S. Geol. Survey Prof. Paper 221-E, p. 67-94.
- Knechtel, M. M., 1949, Geology and coal and natural gas resources of northern Le Flore County, Oklahoma: Oklahoma Geol. Survey Bull. 68, 76 p.
- Merewether, E. A., 1967, Geology of Knoxville quadrangle, Johnson and Pope Counties, Arkansas: Arkansas Geol. Comm. Inf. Circ. 20-E, 55 p.
- Merewether, E. A., and Haley, B. R., 1961, Geology of the Delaware quadrangle, Logan County and vicinity, Arkansas: Arkansas Geol. Comm. Inf. Circ. 20-A, 30 p.
- 1968, Geology of the Coal Hill, Hartman, and Clarksville quadrangles, Johnson County and vicinity, Arkansas: U.S. Geol. Survey Prof. Paper 536-C (in press).
- Miser, H. D., 1954, Geologic map of Oklahoma: U.S. Geol. Survey.
- Oakes, M. C., 1953, Krebs and Cabaniss groups, of Pennsylvanian age, in Oklahoma: Am. Assoc. Petroleum Geologists Bull., v. 37, no. 6, p. 1523-1526.
- Smith, C. D., 1914, Structure of the Fort Smith-Poteau gas field, Arkansas and Oklahoma: U.S. Geol. Survey Bull. 541-B, p. 23-33.
- Snider, L. C., 1914, Geology of east-central Oklahoma, with special reference to the occurrence of petroleum and natural gas: Oklahoma Geol. Survey Bull. 17, 25 p.
- Taff, J. A., 1905, Progress of work in Indian Territory: U.S. Geol. Survey Bull. 260-I, p. 382-401.
- Taff, J. A., and Adams, G. I., 1900, Geology of the eastern Choctaw coal field, Indian Territory: U.S. Geol. Survey 21st Ann. Rept., pt. 2, p. 257-312.
- Trumbull, J. V. A., 1957, Coal resources of Oklahoma: U.S. Geol. Survey Bull. 1042-J, p. 307-382.